



※ L1 confirm by yard.

※ HIGH LEVEL

SPECIFICATION

1. MAX. PRESSURE : 7Kg/cm<sup>2</sup>
2. MAX. TEMPERATURE : 120°C
3. MOUNTING : TOP FLANGE
4. SWITCH : REED SWITCH TYPE
5. VOLTAGE : 250V
6. ENCLOSURE : IP56
7. APPLICATION : WATER & OIL

12	NAME PLATE	BC	1	
11	CABLE GLAND	BC	1	15C
10	REED SWITCH		1	
9	PLATE	PCB	1	
8	MAGNET	FERRITE	2	
7	STOPPER	SUS304	4	
6	SENSOR PIPE	SUS304	1	
5	FLOAT	SUS304	1	
4	SOCKET	SS41	1	
3	FLANGE	SUS304	1	PN16DN50
2	COVER	ALC	1	
1	BODY	ALC	1	
PART NO	PART NAME	MATERIAL	Q'TY	REMARK

ISSUE	A
DATE	7-10-2009
DCR	
DRAWN	JC
CHECKED	

**PSm** Instrumentation Ltd

Haywards Heath, West Sussex RH16 1TW  
 ph: 44 (0) 1444 410040 f: 44 (0) 1444 410121  
<http://www.psm-sensors.co.uk>

SCALE  
NTS

UNLESS OTHERWISE STATED DIMENSIONS ARE IN  
MILLIMETRES / INCHES

TITLE  
Float Switch  
KD30-9-1A-W-G

DRAWING NO  
S-001331-SW-GO

**A4** SHT 1  
OF 1